


Bay/Pierce LED Display Messaging Instructions

Sign Size: 64 px X 32 px

1. Start -> Programs -> LED display -> Msg Editor 3.86
2. Edit -> No Word Wrap (Should NOT be checked)
3. Select “ Normal7(6X7)” from the font dropdown list – this is 6 px wide by 7 pixels high
 - a. Try not to use “Normal5” or smaller
4. Turn Caps Lock on
 - a. Do not use Title Case
5. Type message so that it fills ONE screen instead of scrolling messages – use scrolling for “punchline” type messages
 - a. Scrolling is invoked by:
 - i. Typing a message that extends to the right of the margin
 - ii. Typing too many lines of text
 - iii. Font that is too large
6. Adjust the alignment of the message
7. Click the Pallet icon to change the color of the text (not the Pail icons)
 - a. Do not use blue text
8. Double-click under the word “Pause” on “2 sec” – increase the amount to 4 and click OK
9. Select In Mode
Animation when message enters the sign
10. Select Out Mode
Animation when message exits the sign
11. Decide if you want to Display Marquee
Shows blinking yellow rectangle around message
12. Select Speed
This is speed of the In Mode and Out Mode. Do NOT use a speed slower than Medium Fast
13. Click the Simulator button to preview 
14. Save the message in the appropriate folder on “Elecsign on SVSU5 [U:\]“ Folders are divided by month and department. J.J. will be checking the folder 2-3 times/week for new messages.